

SERIE CO

Modelo / Model / Modèle				P2		I (A)			Ø		Altura manométrica / Height / Hateur (m)													
3~230/400 V	Cod.	1~230 V	Cod.	kW	CV	1 ~ 230V	3 ~ 230V	3 ~ 400V	Asp	Imp	Caudal / Flow / Débit (l/h)	4	6	8	10	12	14	16	18	20	22	24		
CO-350/03 T	7150	CO-350/03 M	7151	0,37	0,5	2,8	2,5	1,5	1½"	1¼"		14600	8000	4000										
CO-350/05 T	7152	CO-350/05 M	7153	0,55	0,75	4,3	2,7	1,6	1½"	1¼"		21000	15000	9500	5000									
CO-350/07 T	7154	CO-350/07 M	7155	0,75	1	4,7	3,6	2,1	1½"	1¼"			20500	15000	9400	5000								
CO-350/09 T	7156	CO-350/09 M	7157	0,9	1,2	5,5	4,2	2,4	1½"	1¼"			24000	19000	13200	8000	2500							
CO-350/II T	7158	CO-350/II M	7159	1,1	1,5	7,9	5,2	3	1½"	1¼"			28500	24000	18000	12000	7000	3000						
CO-350/15 T	7160	CO-350/15 M	7161	1,5	2	9,2	6,3	3,6	1½"	1¼"			36000	28400	24000	18800	13400	7600	4500					
CO-500/15 T	7162	CO-500/15 M	7163	1,5	2	9,1	6,3	3,6		1½"			42000	33000	26500	18000	9000	1000						
CO-500/22 T	7164	CO-500/22 M	7165	2	3	12,7	9,1	5,2	2"	1½"					47000	40500	33000	26000	17600	9000	1500			
CO-500/30 T	7166			3	4	-	11,4	6,6	2"	1½"						52000	44500	38000	30000	23000	15000	8000	2000	