

SERIE DWO

Modelo Model Modèle	Cod.	P2		I (A)			Ø		Caudal / Flow / Débit (l/h)	Altura manométrica / Height / Hauteur (m)												
		kW	CV	1 ~ 230V	3 ~ 230V	3 ~ 400V	Asp	Imp		4	5	6	7	8	9	10	12	14	16	18	20	
HCI-50 M	1089	0,37	0,5	2,0	---	---	1¼"	1"					7200	6300	5100	4000	1300					
HCI-100 T	1090	0,75	1	---	3,1	1,8	1½"	1½"	21000	18500	16000	12000	5000									
HCI-100 M	1091	0,75	1	5,2	---	---	1½"	1½"	21000	18500	16000	12000	5000									
HCI-120 T	1092	1	1,35	---	4,2	2,4	1½"	1½"				20000	17500	15500	11000	3000						
HCI-120 M	1093	1	1,35	6,2	---	---	1½"	1½"				20000	17500	15500	11000	3000						
HCI-150 T	1094	1,1	1,5	---	4,5	2,6	2"	2"		26000	24000	22000	19000	16000	13000	5000						
HCI-150 M	1095	1,1	1,5	7	---	---	2"	2"		26000	24000	22000	19000	16000	13000	5000						
HCI-200 T	1096	1,5	2	---	6,1	3,5	2"	2"			29000	27500	25800	24000	21200	16000	8000					
HCI-200 M	1097	1,5	2	9,2	---	---	2"	2"			29000	27500	25800	24000	21200	16000	8000					
HCI-300 T	1098	2,2	3	---	8,5	4,9	2½"	2"					54000	39000	36000	29000	21000	10000				
HCI-400 T	1099	3	4	---	10,9	6,3	2½"	2"							42000	38000	32000	24000	15000	5000		