

SERIE TAV

| Modelo Model Modèle | Cod. | P2 | | I (A) | | | Ø | | Altura manométrica / Height / Hateur (m) | | | | | | | | | | | | | | | | |
|---------------------------|------|-----|-----|-------------|-------------|-------------|-----|-----|--|-------|-------|-------|-------|-------|-------|-------|------|------|------|------|------|--|--|--|--|
| | | kW | CV | 3 ~ 230V | 3 ~ 400V | 3 ~ 690V | Asp | Imp | Caudal / Flow / Débit (l/h) | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| TAV-37/5 P.L. | 1169 | 1,5 | 2 | 5,8 | 3,4 | - | 1½" | 1½" | | 12000 | 9800 | 7300 | 3000 | | | | | | | | | | | | |
| TAV-37/6 P.L. | 1170 | 2,2 | 3 | 8,1 | 4,7 | - | 1½" | 1½" | | | 10800 | 9000 | 7000 | 2500 | | | | | | | | | | | |
| TAV-37/7 P.L. | 1171 | 2,2 | 3 | 8,1 | 4,7 | - | 1½" | 1½" | | | 11500 | 10000 | 8600 | 6800 | 3000 | | | | | | | | | | |
| TAV-37/8 P.L. | 1172 | 2,2 | 3 | 8,1 | 4,7 | - | 1½" | 1½" | | | 12000 | 10800 | 9600 | 8000 | 6600 | 2500 | | | | | | | | | |
| TAV-37/9 P.L. | 1173 | 3 | 4 | 10,8 | 6,2 | - | 1½" | 1½" | | | 12300 | 11200 | 10200 | 9000 | 7800 | 6200 | 2500 | | | | | | | | |
| TAV-37/10 P.L. | 1174 | 3 | 4 | 10,8 | 6,2 | - | 1½" | 1½" | | | | 11800 | 11000 | 10000 | 9000 | 8000 | 6100 | 2900 | | | | | | | |
| TAV-37/11 P.L. | 1175 | 4 | 5,5 | 13,5 | 7,8 | - | 1½" | 1½" | | | | 12200 | 11500 | 10700 | 9500 | 9000 | 7500 | 6000 | 2000 | | | | | | |
| TAV-37/12 P.L. | 1176 | 4 | 5,5 | 13,5 | 7,8 | - | 1½" | 1½" | | | | 12500 | 11800 | 11000 | 10300 | 9500 | 8500 | 7500 | 6000 | 3000 | | | | | |
| TAV-37/13 P.L. | 1177 | 4 | 5,5 | 13,5 | 7,8 | - | 1½" | 1½" | | | | 13000 | 12100 | 11500 | 10800 | 10000 | 9200 | 8200 | 7200 | 6000 | 2500 | | | | |

| Modelo Model Modèle | Cod. | P2 | | I (A) | | | Ø | | Altura manométrica / Height / Hateur (m) | | | | | | | | | | | | | | | | |
|---------------------------|------|-----|------|-------------|-------------|-------------|-----|-----|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|--|--|
| | | kW | CV | 3 ~ 230V | 3 ~ 400V | 3 ~ 690V | Asp | Imp | Caudal / Flow / Débit (l/h) | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| TAV-73/3 P.L. | 1182 | 3 | 4 | 10,8 | 6,3 | - | 2" | 2" | | 24900 | 20000 | 15000 | 7500 | | | | | | | | | | | | |
| TAV-73/4 P.L. | 1183 | 4 | 5,5 | 13,5 | 7,8 | - | 2" | 2" | | 26400 | 25000 | 20400 | 17500 | 12800 | | | | | | | | | | | |
| TAV-73/5 P.L. | 1185 | 5,5 | 7,5 | - | 11,8 | 6,8 | 2" | 2" | | | 26200 | 23500 | 21500 | 19000 | 16000 | 10000 | | | | | | | | | |
| TAV-73/6 P.L. | 1187 | 5,5 | 7,5 | - | 11,8 | 6,8 | 2" | 2" | | | | 25200 | 24000 | 22000 | 19000 | 17000 | 13600 | 6000 | | | | | | | |
| TAV-73/7 P.L. | 1191 | 7,5 | 10 | - | 15,4 | 8,9 | 2" | 2" | | | | | 25400 | 24600 | 22600 | 21000 | 18800 | 16200 | 12500 | | | | | | |
| TAV-73/8 P.L. | 1193 | 7,5 | 10 | - | 15,4 | 8,9 | 2" | 2" | | | | | | 26500 | 24900 | 23200 | 21400 | 19700 | 17300 | 14500 | 8000 | | | | |
| TAV-73/9 P.L. | 1197 | 9,3 | 12,5 | - | 18,5 | 10,7 | 2" | 2" | | | | | | | 26600 | 25200 | 24500 | 22300 | 20000 | 18200 | 15500 | 12300 | 6000 | | |

| Modelo Model Modèle | Cod. | P2 | | I (A) | | | Ø | | Altura manométrica / Height / Hateur (m) | | | | | | | | | | | | | | | | |
|---------------------------|------|------|------|-------------|-------------|-------------|-----|-----|--|----|----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|--|
| | | kW | CV | 3 ~ 230V | 3 ~ 400V | 3 ~ 690V | Asp | Imp | Caudal / Flow / Débit (l/h) | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| TAV-95/3 P.L. | 1205 | 9,3 | 12,5 | - | 18,5 | 10,7 | 2½" | 2½" | | | | 47000 | 43000 | 40000 | 33000 | 25000 | 5000 | | | | | | | | |
| TAV-95/4 P.L. | 1207 | 15 | 20 | - | 29,4 | 17 | 2½" | 2½" | | | | | 47000 | 43000 | 42000 | 38000 | 33000 | 27000 | 15000 | | | | | | |
| TAV-95/5 P.L. | 1211 | 15 | 20 | - | 29,4 | 17 | 2½" | 2½" | | | | | | 47000 | 44000 | 43000 | 40000 | 37000 | 33000 | 28000 | 20000 | 5000 | | | |
| TAV-95/6 P.L. | 1213 | 18,5 | 25 | - | 34 | 19,6 | 2½" | 2½" | | | | | | | 45000 | 43000 | 42000 | 38000 | 37000 | 33000 | 28000 | 21000 | 12500 | | |