

## SERIE INOX-PALM

Modelo Model Modèle	Cod.	P1		P2		I (A)		Ø Imp	Caudal / Flow / Débit (l/h)	Altura manométrica / Height / Hauteur (m)											Ø Sólidos Solids Solides (mm)	
		kW	kW	CV	1~ 230V	3~ 400V	0			1	2	3	4	5	6	7	8	9	10	11		
INOX-PALM IA	1228	0,77	0,6	<b>0,8</b>	3,5	-	1¼" V	Caudal / Flow / Débit (l/h)	14400	13200	12000	10200	8400	6100	3600	1200						35
INOX-PALM 2A	1227	1,1	0,88	<b>1,2</b>	5,2	-	1½" V		22000	21000	19500	18000	16000	14000	12000	9000	5500	4500	3000	1200		35
INOX-PALM 2	1210	0,92	0,88	<b>1,2</b>	-	1,8	1½" V		22000	21000	19500	18000	16000	14000	12000	9000	5500	4500	3000	1200		35

Modelo Model Modèle	Cod.	P1		P2		I (A)		Ø Imp	Caudal / Flow / Débit (l/h)	Altura manométrica / Height / Hauteur (m)											Ø Sólidos Solids Solides (mm)		
		kW	kW	CV	1~ 230V	3~ 400V	2			4	6	8	10	11	12	13	15	17	18	19			
INOX-PALM 2.5A	1692	1,6	1,1	<b>1,5</b>	7,5	-	2" H	Caudal / Flow / Débit (l/h)	28500	26000	24000	15000	6000	3000								40	
INOX-PALM 2.5	1693	1,6	1,1	<b>1,5</b>	-	3,0	2" H		28500	26000	24000	15000	6000	3000									40
INOX-PALM 3A	1694	1,6	1,1	<b>1,5</b>	7,5	-	2" H		32000	25000	20000	14000	9000	3000									45
INOX-PALM 3	1695	1,65	1,1	<b>1,5</b>	-	3,0	2" H		32000	25000	20000	14000	9000	3000									45
INOX-PALM 4A	1696	1,95	1,5	<b>2</b>	10,5	-	2" H		45000	36000	32000	27000	22000	17000	12000	6000							45
INOX-PALM 4	1697	1,92	1,5	<b>2</b>	-	3,4	2" H		45000	36000	32000	27000	22000	17000	12000	6000							45
INOX-PALM 5	1698	3	2,2	<b>3</b>	-	5,6	2" H		50000	45000	40000	37000	33000	30000	26000	23000	21000	13000	8000	1000		45	