

SERIE SUB-C

Modelo Model Modèle	P2		I (A)				Ø Imp	Caudal / Flow / Débit (l/h)	Altura manométrica / Height / Hauteur (m)											
	kW	CV	1 ~ 230V	3 ~ 230V	3 ~ 400V	3 ~ 690V			5	10	15	20	25	30	35	40	45	50		
SUB-C-25 M	1,85	2,5	13	-	-	-	2"	25000	20500	15500	8000									
SUB-C-25	1,85	2,5	-	7,3	4,2	-	2"	25000	20500	15500	8000									
SUB-C-40	3	4	-	11,2	6,5	-	3"	49500	42000	33500	23000	10000								
SUB-C-80	6	8	-	-	13	7,5	3"	100000	94000	83000	65000	40000	10000							
SUB-C-40/2	3	4	-	11,2	6,5	-	2"		25000	22500	20000	18000	15000	12000	8000					
SUB-C-80/2	6	8	-	-	13	7,5	3"		44000	42000	38000	34000	31000	25000	20000	14000	5000			

Modelo Model Modèle	P2		I (A)				Ø Imp	Caudal / Flow / Débit	Altura manométrica / Height / Hauteur (m)											
	kW	CV	1 ~ 230V	3 ~ 230V	3 ~ 400V	3 ~ 690V			0	2	4	6	8	10	12	13	14	15		
SUB-C-25 D M	1,85	2,5	13	-	-	-	3"	52000	50400	45000	40000	35000	28000	20500	15000					
SUB-C-25 D	1,85	2,5	-	7,3	4,2	-	3"	52000	50400	45000	40000	35000	28000	20500	15000					
SUB-C-40 D	3	4	-	11,2	6,5	-	3"	70000	68000	65000	60300	56000	50000	40000	36000	31000	20000			