

## SERIE BM

Modelo Model Modèle	Cod.	P2		Ø		Caudal / Flow / Débit (l/h)	Altura manométrica / Height / Hateur (m)										
		kW	CV	Asp	Imp		0	2	5	8	10	15	20	25	30	35	40
<b>BC-12 (12V)</b>	1065	0,06	<b>1/12</b>	20	20	1800	1800	1680	1200								
<b>BC-12 (24V)</b>	1066	0,06	<b>1/12</b>	20	20	1800	1800	1680	1200								
<b>BC-12 C (12V)</b>	1076	0,06	<b>1/12</b>	20	20	720	680	640	600	540	480	420					
<b>BC-12 C (24V)</b>	1077	0,06	<b>1/12</b>	20	20	720	680	640	600	540	480	420					
<b>BT-20</b>	1067	0,10	<b>1/8</b>	20	20	2100	1900	1850	1740	1380	1200						
<b>BM-20</b>	1069	0,10	<b>1/8</b>	20	20	2100	1900	1850	1740	1380	1200						
<b>BT-40</b>	1070	0,37	<b>0,5</b>	20	20	1500	1480	1440	1430	1380	1320	1260	1200	1140	1020	900	
<b>BM-40</b>	1072	0,37	<b>0,5</b>	20	20	1500	1480	1440	1430	1380	1320	1260	1200	1140	1020	900	
<b>BT-60</b>	1073	0,37	<b>0,5</b>	25	25	3600	3450	3300	3200	3000	2400						
<b>BM-60</b>	1075	0,37	<b>0,5</b>	25	25	3600	3450	3300	3200	3000	2400						