



CI25.3-8



P 150.2-10



**Poseidón
2-29 XT**



**Poseidón
4-30 XT**



**Poseidón
5-62 PA**

APLICACIONES

Electrobombas de pistones semi-industriales, portátiles y de elevadas prestaciones. Potentes y manejables, aptas para la limpieza a alta presión.

CARACTERÍSTICAS TÉCNICAS

Bombas de alta presión con 3 pistones recubiertos de cerámica.
Cabezal de bomba en latón.
Motor sin mantenimiento con protección térmica incorporada.
Válvula by-pass.
Regulación continua de la presión.
Cable eléctrico de alimentación de 5 m con enchufe.

ACCESORIOS OPCIONALES

Cepillo de limpieza rotativa.
Desatascador de tuberías.

APPLICATIONS

Semi-industrial piston electro-pumps. Portable and high performance pump. Powerful and easy-to-use. Suitable for high pressure cleaning.

TECHNICAL CHARACTERISTICS

High pressure pump with 3 pistons in ceramics coating.
Brass pump head.
Maintenance-free motor with built-in thermal protection.
By-pass valve.
Continuous pressure regulation.
5 m power cable with plug.

OPTIONAL ACCESSORIES

Rotation cleaning brush.
Pipe plunger.

Características <i>Characteristics / Caractéristiques</i>	CI25.3-8	P 150.2-10	Poseidón 2-29 XT	Poseidón 4-30 XT	Poseidón 5-62 PA
Presión / Pressure / Pression (bar)	125	150	160	160	220
Caudal / Flow / Débit (l/h)	520	610	600	620	1130
r.p.m.	2.800	2.800	2.800	1.450	1.450
Tª max. agua / Tª max. water / Tª max. eau (°C)	40	60	60	60	60
Altura máxima aspiración (m) <i>Max. height aspiration Hateur max. aspiration</i>	0	0	1	1,5	1
Manguera alta presión (m) <i>High pressure hose Tuyau d'arrosage haut pression</i>	8	10	15	15	10
Boquilla adicional rotativa <i>Additional rotary mouthpiece Embouchure rotatoire supplémentaire</i>	✓	✓	✓	✓	✗
Aspiración de jabón <i>Aspiration of soap / Aspiration de savon</i>	✓	✓	✓	✓	✓
Potencia / Power / Puissance (kW)	1,8	2,9	3,3	3,8	7,4
Tensión / Voltage (V)	II 230	II 230	II 230	II 230	III 400
Peso / Weight / Poids (kg)	10,7	29,5	24,5	46	78
Dimensiones / Dimensions (mm)	280x250x850	495x380x975	394x391x955	400x400x1030	735x570x1020